




FEATURES

- ※Low profile 1.6mm height
- ※Gold contact for high reliability
- ※Top tape type for washing process


APPLICATION

- ※Industrial control
- ※Automatic machines control
- ※NB, electronic devices

SPECIFICATION

Contact Rating	25mA, 24V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	300V AC/1 minute
Operating Force	500gf max.
Travel	0.6mm
Operating Life	1,000 cycles
Operating Temp.	-40°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

CIRCUIT



PACKAGE


<Tube>

DNH(F)-02: 125 pcs
DNH(F)-04: 75 pcs
DNH(F)-06: 54 pcs
DNH(F)-08: 40 pcs
DNH(F)-10: 33 pcs



<Tape & Reel>

DNH: 4000 pcs
DNHF: 2500 pcs



HOW TO ORDER



DNH



P.C.B. LAYOUT





PART NO.	NO.OF POS	DIM A
DNH-02	2	3.77
DNH-04	4	6.31
DNH-06	6	8.85
DNH-08	8	11.39
DNH-10	10	13.93



1.6mm
Half Pitch Type



DHNF



P.C.B. LAYOUT



PART NO.	NO.OF POS	DIM A
DHNF-02	2	3.77
DHNF-04	4	6.31
DHNF-06	6	8.85
DHNF-08	8	11.39
DHNF-10	10	13.93